

**Vehicle having a roof assembly and such roof assembly**

**Patent number:** DE20204110U  
**Publication date:** 2002-09-12  
**Inventor:**  
**Applicant:** INALFA IND BV (NL)  
**Classification:**  
**- international:** B60J7/02; B60J7/047; B60J7/02; B60J7/04; (IPC1-7):  
B60J7/08; B60J1/18  
**- european:** B60J7/02G2; B 60J7/047  
**Application number:** DE20022004110U 20020314  
**Priority number(s):** DE20022004110U 20020314

**Report a data error here**

Abstract not available for DE20204110U

Abstract of corresponding document: **US2005140164**

A vehicle has a roof assembly ( 4 ) opening an opening ( 17 ) in the vehicle roof which includes at least a rear cross beam ( 12 ). The roof assembly comprises at least one closure element ( 8,9,10 ) which is at least one closure element ( 8,9,10 ) which is at least movable between a closed position for closing the roof opening, and an open, rearwardly displaced position, in which the roof opening is at least partially released. The rear cross beam ( 12 ) is connected to pivotable arms ( 13 ) which are at least pivotally attached to the body ( 1 ). The at least one closure element ( 8,9,10 ), when in the open position, forms a unit ( 15 ) with said rear cross beam ( 12 ). The unit ( 15 ) is pivotable by means of said arms ( 13 ) between an operative position at the roof and an inoperative position in the trunk ( 3 ) of the vehicle.

---

Data supplied from the **esp@cenet** database - Worldwide